

Steel Stabilizing Jack with Solid Foam Wheels 100,000 Lb. Static Capacity Yellow

MODEL CJ-BEAM-SN

Loading Dock Equipment / Trailer Stabilizing Jacks



PRODUCT OVERVIEW

Trailer stabilizing jacks are used to prevent up-ending of semi-trailers when they are not connected to a tractor during loading and unloading operations. Throughout the loading and unloading process it is always recommended to use two jacks, one on each side of the front of the trailer. The trailer must be situated on a flat, stable and improved (preferably concrete) surface, while the jack sits perpendicular to the underside of the trailer. Every jack is built of a high strength steel construction with a flush-type Zerk fitting for lubricating ACME screw. A yellow powder coat finish and a reflective collar for visibility at night are both included. Each jack meets OSHA regulations when used with wheel chocks. **The color of handles included with...

KEY FEATURES

- Rectangle top plate
- Reflective collar increases visibility at night
- Manual raising and lowering mechanism
- Meets OSHA regulations when used with wheel chocks

CORE PRODUCT DATA

ASSEMBLED WEIGHT
197 lbs

ASSEMBLED SIZE
29.75" W x 27.375" L x 41" H

SHIP WEIGHT
238 lbs

PACKAGE 1 SIZE
40" W x 48" D x 46" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Static Capacity (lb.)	100,000
Uniform Lifting Capacity (lb.)	50,000
Lowered Height (in.)	41
Raised Height (in.)	55
Wheel Size (in.)	16
Wheel Type	Solid Foam
Beam Length (in.)	4-3/8
Beam Width (in.)	29-3/4
Beam Thickness (in.)	3/8
Operation	Hand Crank

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=90>