

# Vinyl Dock Seal 16 In. 8 Ft. x 8 Ft. Black

**MODEL D-150-16**

Loading Dock Equipment / Dock Seals

## PRODUCT OVERVIEW

The superior nylon reinforced vinyl facing has a higher tear strength than equivalent weight hypalon. The chemically sealed ends prevent moisture infiltration. It is mounted on and bonded on a durable wolmanized wood and contains a full height air escape tunnel. The unit consists of a three (3) piece construction with beveled fronts and a through the wall installation kit that is included. Five (5") maximum compression is recommended. Application with a flush dock to building in conjunction with an Edge-O-Dock use a twenty (20) inch projection Dock Seal. To ensure proper size complete the survey sheet. This unit is non-returnable.

## KEY FEATURES

- Three foam-filled pads offer full dock protection
- Maximum compression design offers the maximum protection
- Built-in air tunnels allow air to escape when contacted by a trailer
- Mounting hardware and installation instructions make installation quick and easy

## CORE PRODUCT DATA

|                                                                                                                                                 |                                                         |                                              |
|-------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|----------------------------------------------|
| <b>ASSEMBLED WEIGHT</b><br><b>128 lbs</b>                                                                                                       | <b>ASSEMBLED SIZE</b><br><b>120" W x 16" L x 108" H</b> | <b>SHIP WEIGHT</b><br><b>221 lbs</b>         |
| <b>PACKAGE 1 SIZE</b><br><b>36" W x 120" D x 22" H</b>                                                                                          | <b>COLOR / FINISH</b><br><b>Black</b>                   | <b>FREIGHT TYPE</b><br><b>LTL Palletized</b> |
| <b>AVAILABILITY</b> Available<br>Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering. |                                                         | <b>QUICKSHIP: --</b>                         |

PRODUCT SPECIFICATIONS

|                                     |       |
|-------------------------------------|-------|
| Projection (in.)                    | 16    |
| Nylon Reinforced Vinyl (oz.)        | 36    |
| Nylon Reinforced Guide Strips (in.) | 2     |
| Top Height (in.)                    | 12    |
| Side Wall Width (in.)               | 9-1/2 |
| Face Width (in.)                    | 12    |
| Maximum Compression (in.)           | 5     |
| Standard Guide Stipe Height (in.)   | 30    |
| Side Height (in.)                   | 96    |
| Max Door Width (in.)                | 96    |
| Max Door Height (in.)               | 96    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=19>