

# Steel Leveling Jack 18 In. 5000 Lb. Capacity Silver

**MODEL LJ-9**

Industrial Carts & Dollies / Leveling Jacks



## PRODUCT OVERVIEW

This leveling jack is designed for permanent installation, screw-style jack hold platforms and other equipment in place and stabilize them at the required height. Drill a one and one quarter inch (1-1/4") diameter hole through the platform to be leveled and bolt the platform between the upper and lower flanges of the jack's divided housing. Jack has a handle that folds down when not in use. Swivel base has a slip-resistant rubber pad on the bottom (replacement pads available).

## KEY FEATURES

- Lifting design raises, levels and stabilizes portable equipment
- Rubber bottom pad provides extra grip
- Jack handle design folds down when not in use
- Designed for permanent installation

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**9 lbs**

ASSEMBLED SIZE  
**9" W x 4.5" L x 26.59375" H**

SHIP WEIGHT  
**11 lbs**

PACKAGE 1 SIZE  
**5" W x 20" D x 5" H**

COLOR / FINISH  
**Silver**

FREIGHT TYPE  
**Parcel**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |        |
|--------------------------------------|--------|
| Uniform Capacity (lb.)               | 5,000  |
| Handle Length (in.)                  | 8-1/2  |
| Swivel Base Diameter (in.)           | 3-7/8  |
| Screw Diameter (in.)                 | 1-1/4  |
| Lift Rate Per Crank Revolution (in.) | 1/4    |
| Minimum Extended Height (in.)        | 4-1/2  |
| Maximum Extended Height (in.)        | 13-1/2 |
| Screw Travel (in.)                   | 9      |
| Thread Size (millimeter)             | 4      |
| Holding Capacity (pounds)            | 10,000 |
| Jaw Opening (in.)                    | 3-1/4  |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1061>