

# Galvanized Steel Winch Truck Jib Crane 500 Lb. Extended Capacity Gray

**MODEL WTJ-2-G**

Overhead Lifting / Winch Operated Truck Jib Cranes

## PRODUCT OVERVIEW

This Galvanized winch operated truck Jib crane lifts items from ground to truck bed height, then rotate into cargo area. Includes telescopic boom design with manual hydraulic hand pump to pivot boom up and down. Manual cable winch to lift and lower loads. Unit comes with one grab hook, one chain slot lock, and one sling hook with latch. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**125 lbs**

**ASSEMBLED SIZE**  
**32.875" W x 11" L x 59.5" H**

**SHIP WEIGHT**  
**134 lbs**

**PACKAGE 1 SIZE**  
**12" W x 65" D x 17" H**

**COLOR / FINISH**  
**Gray**

**FREIGHT TYPE**  
**LTL Loose**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                          |        |
|------------------------------------------|--------|
| Uniform Cable Winch Capacity (lb.)       | 500    |
| Extended Fixed Hook Capacity (lb.)       | 500    |
| Extended Usable Reach (in.)              | 52     |
| Extended Maximum Hook Height (in.)       | 99     |
| Extended Minimum Hook Height (in.)       | Zero   |
| Retracted Fixed Hook Capacity (lb.)      | 1,000  |
| Retracted Usable Reach (in.)             | 30-1/2 |
| Retracted Maximum Hook Height (in.)      | 84     |
| Retracted Minimum Hook Height (in.)      | 12-1/2 |
| Overall Cable Length (ft.)               | 32     |
| Usable Cable Length (ft.)                | 24     |
| Cable Diameter (in.)                     | 3/16   |
| Mounting Plate Length (in.)              | 11     |
| Mounting Plate Width (in.)               | 11     |
| Base Height (in.)                        | 11-1/2 |
| Rotation (degrees)                       | 360    |
| Piston Stroke (in.)                      | 16-3/8 |
| Piston Stroke Per Pump (in.)             | 1/16   |
| Cable Retracts/Extension Per Crank (in.) | 1-1/2  |
| Number of Cranks to Retract/Extend Cable | 72     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=578>