# Galvanized Steel AC Powered Jib Crane CSA Compliant 3-1/2 to 5-1/2 Ft. Boom 1,500 lb. Capacity Gray

**MODEL WTJ-E-15-3-AC-CSA-GA**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

The power lift Jib cranes are designed for material handling applications on docks, in warehouses or in truck beds. Choose either 12V DC, 1 HP with 6-foot long removable pendant control or 115V AC 1/3 HP with fingertip switch to raise and lower hook. Meets ANSI and OSHA specifications. 12" x 12" mounting plate. Units are not rated for overhead lifting applications. Consult factory for pricing if overhead lifting rating is required. Intermittent use cranes feature rotation hand brakes that offer unlimited 360 degrees positioning. Mast mounts permanently. Boom adjusts in 12" increments and can be positioned at 4 elevations. The AC units feature 25 feet of 7/32" cable. Folds for storage.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**176 lbs** | ASSEMBLED SIZE<br>**18.6875" W x 66.75" L x 67.5" H** | SHIP WEIGHT<br>**223 lbs** |
| PACKAGE 1 SIZE<br>**29" W x 66" D x 17" H** | COLOR / FINISH<br>**Gray** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 1500 |
| **Boom Reach (in.)** | 43-1/16 to 66-3/4 |
| **Boom Height (in.)** | 47-1/8 to 73-5/16 |
| **Rotation Degree** | 360 |
| **Boom Adjustment Increments (in.)** | 12 |
| **Cable Length (ft.)** | 25 |
| **Cable Diameter (in.)** | 7/32 |
| **AC (volts)** | 115 |
| **Horsepower (HP)** | 1/3 |
| **Mounting Plate Length (in.)** | 12 |
| **Mounting Plate Width (in.)** | 12 |
| **1,500 lb. Capacity at Boom Extension (in.)** | 27-13/16 |
| **Capacity at 47-1/8" Fully Retracted (lbs.)** | 650 |
| **Capacity at 47-1/8" Mid-Position (lbs.)** | 300 |
| **Capacity at 47-1/8" Fully Extended (lbs.)** | 200 |
| **Capacity at 56-3/16" Fully Retracted (lbs.)** | 1100 |
| **Capacity at 56-3/16" Mid-Position (lbs.)** | 650 |
| **Capacity at 56-3/16" Fully Extended (lbs.)** | 550 |
| **Capacity at 64-3/4" Fully Retracted (lbs.)** | 1,250 |
| **Capacity at 64-3/4" Mid-Position (lbs.)** | 850 |
| **Capacity at 64-3/4" Fully Extended (lbs.)** | 650 |
| **Capacity at 73-5/16" Fully Retracted (lbs.)** | 1500 |
| **Capacity at 73-5/16" Mid-Position (lbs.)** | 1150 |
| **Capacity at 73-5/16" Fully Extended (lbs.)** | 800 |
| **Compliant** | CSA |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=582