

# Galvanized Steel DC Powered Jib Crane 3-1/2 to 5-1/2 Ft. Boom 1,500 Lb. Capacity Gray

**MODEL WTJ-E-15-3-DC-GAL**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

The Jib crane is ideal for lifting objects in a variety of areas. With a steel construction and a galvanized finish, the jib crane also features a telescopic boom with an adjustable length and height, manual boom rotation, powered cable winch for easy lifting and maneuvering, and a plug in handheld winch control. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**200 lbs**

**ASSEMBLED SIZE**  
**13.5" W x 51.0625" L x 65.6875" H**

**SHIP WEIGHT**  
**213 lbs**

**PACKAGE 1 SIZE**  
**29" W x 65" D x 17" H**

**COLOR / FINISH**  
**Gray**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                             |                   |
|---------------------------------------------|-------------------|
| Uniform Capacity (lb.)                      | 1,500             |
| Boom Reach (in.)                            | 43-1/16 to 66-3/4 |
| Boom Height (in.)                           | 47-1/8 to 73-5/16 |
| Rotation Degree                             | 360               |
| DC (volts)                                  | 12                |
| Horsepower                                  | 1                 |
| Wire Rope Length (ft.)                      | 46                |
| Wire Rope Diameter (in.)                    | 3/16              |
| Mounting Plate Length (in.)                 | 12                |
| Mounting Plate Width (in.)                  | 12                |
| 1,500 lb. Capacity at Boom Extension (in.)  | 27-13/16          |
| Capacity at 47-1/8" Fully Retracted (lbs.)  | 650               |
| Capacity at 47-1/8" Mid-Position (lbs.)     | 300               |
| Capacity at 47-1/8" Fully Extended (lbs.)   | 200               |
| Capacity at 56-3/16" Fully Retracted (lbs.) | 1100              |
| Capacity at 56-3/16" Mid-Position (lbs.)    | 650               |
| Capacity at 56-3/16" Fully Extended (lbs.)  | 550               |
| Capacity at 64-3/4" Fully Retracted (lbs.)  | 1,250             |
| Capacity at 64-3/4" Mid-Position (lbs.)     | 850               |
| Capacity at 64-3/4" Fully Extended (lbs.)   | 650               |
| Overall Width (in.)                         | 13-1/2            |
| Overall Retracted Length (in.)              | 51                |
| Overall Height (in.)                        | 65-11/16          |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>